

JINDAL



BLACK & GALVANIZED STEEL TUBES CONFORMING TO  IS: 1239(I)

N.B and Series	Wall Thickness	Outside Die		Nominal Weight		N.B and Series	Wall Thickness	Outside Die		Nominal Weight			
				P/E	S/S					P/E	S/S		
MM	MM	Min	Max	Kg/m	Kg/m	MM	MM	Min	Max	Kg/m	Kg/m		
15	L	2.0	21.0	21.4	0.947	0.956	50	L	2.9	59.6	60.2	4.08	4.15
	M	2.6	21.0	21.8	1.21	1.22		M	3.6	59.7	60.8	5.03	5.10
	H	3.2	21.0	21.8	1.44	1.45		H	4.5	59.7	60.8	6.19	6.26
20	L	2.3	26.4	26.9	1.38	1.39	65	L	3.2	75.2	76.0	5.71	5.83
	M	2.6	26.5	27.3	1.56	1.57		M	3.6	75.3	76.6	6.42	6.54
	H	3.2	26.5	27.3	1.87	1.88		H	4.5	75.3	76.6	7.93	8.05
25	L	2.6	33.2	33.8	1.98	2.00	80	L	3.2	87.9	88.7	6.72	6.89
	M	3.2	33.3	34.2	2.41	2.43		M	4.0	88.0	88.5	8.36	8.53
	H	4.0	33.3	34.2	2.93	2.95		H	4.8	88.0	88.5	9.90	10.10
32	L	2.6	41.9	42.5	2.54	2.57	100	L	3.6	113.0	113.9	9.75	10.00
	M	3.2	42.0	42.9	3.10	3.13		M	4.5	113.1	115.0	12.20	12.50
	H	4.0	42.0	42.9	3.79	3.82		H	5.4	113.1	115.0	14.50	14.80
							125	M	4.8	138.5	140.8	15.90	16.40